









Article no.	Designation	Length L [mm (inch)]		Stroke [mm (inch)]		L2 [mm (inch)]		Moving mass [g (lb)]		Total weight [g (lb)]	
0150-5827	DM03-48x150G-HP-C-65__CS10__MS02	308	(12.13)	65	(2.56)	0	(0)	2690	(5.80)	6850	(15.10)
0150-5790	DM03-48x150G-HP-C-65__CS10__MS03										
0150-5791	DM03-48x150G-HP-C-65__CS10__MS04										
0150-5766	DM03-48x150G-HP-C-65__CS10__MS06	308	(12.13)	65	(2.56)	0	(0)	2740	(6.04)	6900	(15.21)
0150-5788	DM03-48x150G-HP-C-65__CS10__MS07										
0150-5869	DM03-48x150G-HP-C-65__CS10__MS09										
0150-5828	DM03-48x150G-HP-C-65__CS10__MS31	308	(12.13)	65	(2.56)	0	(0)	2740	(6.04)	7450	(16.42)
0150-5870	DM03-48x150G-HP-C-65__CS10__MS34										
0150-5786	DM03-48x150G-HP-C-65__CS10__MS36										
0150-25827	DM03-48x150G-HP-C-65__CS10__MS02-2S	308	(12.13)	65	(2.56)	0	(0)	2690	(5.80)	6850	(15.10)
0150-25790	DM03-48x150G-HP-C-65__CS10__MS03-2S										
0150-25791	DM03-48x150G-HP-C-65__CS10__MS04-2S										
0150-5830	DM03-48x150G-HP-C-125__CS10__MS02	368	(14.49)	125	(4.92)	0	(0)	3180	(7.01)	7750	(17.09)
0150-5793	DM03-48x150G-HP-C-125__CS10__MS03										
0150-5794	DM03-48x150G-HP-C-125__CS10__MS04										
0150-5767	DM03-48x150G-HP-C-125__CS10__MS06	368	(14.49)	125	(4.92)	0	(0)	3300	(7.28)	7870	(17.35)
0150-5792	DM03-48x150G-HP-C-125__CS10__MS07										
0150-5871	DM03-48x150G-HP-C-125__CS10__MS09										
0150-5831	DM03-48x150G-HP-C-125__CS10__MS31	368	(14.49)	125	(4.92)	130.5	(5.14)	3420	(7.54)	8950	(19.73)
0150-5787	DM03-48x150G-HP-C-125__CS10__MS34										
0150-5872	DM03-48x150G-HP-C-125__CS10__MS36										
0150-25830	DM03-48x150G-HP-C-125__CS10__MS02-2S	368	(14.49)	125	(4.92)	0	(0)	3180	(7.01)	7750	(17.09)
0150-25793	DM03-48x150G-HP-C-125__CS10__MS03-2S										
0150-25794	DM03-48x150G-HP-C-125__CS10__MS04-2S										
0150-5832	DM03-48x150G-HP-C-185__CS10__MS02	428	(16.85)	185	(7.28)	66.5	(2.62)	3420	(7.54)	8780	(19.36)
0150-5796	DM03-48x150G-HP-C-185__CS10__MS03										
0150-5797	DM03-48x150G-HP-C-185__CS10__MS04										
0150-5768	DM03-48x150G-HP-C-185__CS10__MS06	428	(16.85)	185	(7.28)	10	(0.39)	3790	(8.36)	8820	(19.44)
0150-5873	DM03-48x150G-HP-C-185__CS10__MS07										
0150-5874	DM03-48x150G-HP-C-185__CS10__MS09										
0150-5833	DM03-48x150G-HP-C-185__CS10__MS31	428	(16.85)	185	(7.28)	225.5	(8.88)	3950	(8.71)	10050	(22.16)
0150-5875	DM03-48x150G-HP-C-185__CS10__MS34										
0150-5876	DM03-48x150G-HP-C-185__CS10__MS36										
0150-25832	DM03-48x150G-HP-C-185__CS10__MS02-2S	428	(16.85)	185	(7.28)	66.5	(2.62)	3420	(7.54)	8780	(19.36)
0150-25796	DM03-48x150G-HP-C-185__CS10__MS03-2S										
0150-25797	DM03-48x150G-HP-C-185__CS10__MS04-2S										
0150-5843	DM03-48x150G-HP-C-275__CS10__MS02	518	(20.39)	275	(10.83)	130.5	(5.14)	4450	(9.81)	9980	(22.00)
0150-5931	DM03-48x150G-HP-C-275__CS10__MS03										
0150-5877	DM03-48x150G-HP-C-275__CS10__MS04										
0150-5834	DM03-48x150G-HP-C-275__CS10__MS06	518	(20.39)	275	(10.83)	130.5	(5.14)	4720	(10.41)	10250	(22.60)
0150-5878	DM03-48x150G-HP-C-275__CS10__MS07										
0150-5879	DM03-48x150G-HP-C-275__CS10__MS09										
0150-25843	DM03-48x150G-HP-C-275__CS10__MS02-2S	518	(20.39)	275	(10.83)	130.5	(5.14)	4450	(9.81)	9980	(22.00)
0150-25931	DM03-48x150G-HP-C-275__CS10__MS03-2S										
0150-25877	DM03-48x150G-HP-C-275__CS10__MS04-2S										

1:5



1:5





Rev.	Change	Date	Author	Appr.
A	Document created	18.11.2026	sm	jb

General tolerance DIN ISO 2768 - mK	Created by NTI AG	Status 18.11.2026/sm	Material
LinMot®	File name 0184-0039__DM03-48x150G-HP-C-XXX__CS10__MSxx (-2S)		Weight (g)
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	Title, additional title DM03-48x150G-HP-C-XXX__CS10__MSxx (-2S)		Document type Assembly drawing
	Technical Drawing DM03-48x150___CS10__MSxx (-2S)		Drawing number / Index 0184-0039 A
Template type: SW2026 Version: V1.1 NTI_EN__A2__0__Horizontal__Sheet__format__V1.1	Art.No.: See table	Scale 1:2	Sheet 1 / 3 A2

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.





LABEL	X-POSITION	Y-POSITION	SIZE
A1	-20	17	M6 ↧ 15
A2	-20	57	
A3	-20	97	
A4	-20	137	
A5	20	17	
A6	20	57	
A7	20	97	
A8	20	137	
B1	-16	37	∅ 5 H7 +0.012 0 ↧ 10
B2	16	37	
C1	-18	27	∅ 6.6 ↧ 15 ⌴ ∅ 11 ↧ 6.4
C2	-18	77	
C3	-18	127	
C4	18	27	
C5	18	77	
C6	18	127	
D1	-16	71	∅ 5 H7 +0.012 0 ↧ 5
D2	-16	83	
D3	-16	117.50	
D4	16	71	
D5	16	83	
D6	16	117.50	

For dowel pin holes


⌖	∅ 0.1	A	B	C

Rev.	Change	Date	Author	Appr.
A	Document created	18.11.2026	sm	jb

General tolerance DIN ISO 2768 - mK	Created by NTI AG	Status 18.11.2026/sm	Material
LinMot®	0184-0039_DM03-48x150G-HP-C-XXX_CS10_MSxx (-2S)		Weight (g)
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	Title, additional title DM03-48x150G-HP-C-XXX_CS10_MSxx (-2S) Technical Drawing DM03-48x150___CS10_MSxx (-2S)	Document type Assembly drawing Drawing number / Index 0184-0039 A	
Template type: SW2026 Version: V1.1 NTI_EN_A3_Q_Horizontal_Sheet_format_V1.1	Art.No.: See table	Scale 1:1	Sheet 2 / 3 A3

LABEL	Z-POSITION	Y-POSITION	SIZE
E1	35.50	6	M8 ↧ 12
E2	35.50	131	
E3	105.50	6	
E4	105.50	131	
E5	175.50	6	
E6	175.50	131	
F1	42.50	36	M6 ↧ 12
F2	42.50	91	
F3	104.50	36	
F4	104.50	91	
F5	166.50	36	
F6	166.50	91	
G1	81	34	∅ 5 +0.012 0 H7 ↧ 8
G2	160	34	
H1	87.50	21.50	M4 ↧ 8
H2	87.50	93	
H3	159	21.50	
H4	159	93	
J1	28	20	M4 ↧ 8
J2	38	19.93	
K1	9	91.50	M5 ↧ 10
K2	34	91.50	

LABEL	Z-POSITION	X-POSITION	SIZE
L1	45	-20	M8 ↧ 16
L2	45	20	
L3	95	-20	
L4	95	20	
L5	145	-20	
L6	145	20	
L7	195	-20	
L8	195	20	
M1	76	-18	M6 ↧ 12
M2	76	18	
M3	126	-18	
M4	126	18	
M5	176	-18	
N1	93	0	∅ 5 +0.012 0 H7 ↧ 10
N2	115	-16	
N3	148	0	
N4	166	-16	
N5	166	16	
P1	89	-15	M6 ↧ 12
P2	89	15	
P3	159	-15	
P4	159	15	



For dowel pin holes

⌖	∅ 0.1	D	E	F

Rev.	Change	Date	Author	Appr.
A	Document created	18.11.2026	sm	jb

General tolerance DIN ISO 2768 - mK	Created by NTI AG	Status 18.11.2026/sm	Material
LinMot®	File name 0184-0039_DM03-48x150G-HP-C-XXX_CS10_MSxx (-2S)		Weight (g)
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	Title, additional title DM03-48x150G-HP-C-XXX_CS10_MSxx (-2S)		Document type Assembly drawing
	Technical Drawing DM03-48x150___CS10_MSxx (-2S)		Drawing number / Index 0184-0039 A
Template type: SW2026 Version: V1.1 NTI_EN_A2_Q_Horizontal_Sheet_format_V1.1	Art.No.: See table	Scale 1:1	Sheet 3 / 3 A2

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.