



L _(mm)	Stroke with PS0x-23(S)x80	Stroke with PS0x-23x160	Standard HP-L	Art.-No.
	SS(ES) _(mm)	SS(ES) _(mm)		
130	0(60)	-	PL01-12x130!90-HP-L	0150-3687
170	40(100)	-	PL01-12x170!130-HP-L	0150-3688
200	70(130)	10*(130)	PL01-12x200!160-HP-L	0150-3689
230	100(160)	20(160)	PL01-12x230!190-HP-L	0150-2546
270	140(200)	60(200)	PL01-12x270!230-HP-L	0150-2557
290	160(220)	80(220)	PL01-12x290!250-HP-L	0150-3690
350	220(280)	140(280)	PL01-12x350!310-HP-L	0150-3691
420	290(350)	210(350)	PL01-12x420!380-HP-L	0150-3692
480	350(410)	270(410)	PL01-12x480!440-HP-L	0150-3693
580	450(510)	370(510)	PL01-12x580!540-HP-L	0150-3694
760	630(690)	550(690)	PL01-12x760!720-HP-L	0150-3695

*-reduzierte Force

Allgemeintoleranzen ISO 2768-m	PL01-12x...-HP-L		Material:	
	Hollow Slider		Ersatz für:	
			Status: 20.04.2016/dm	
			Änderungen	
Gezeichnet:	20.4.2016	D.Marinkovic		
Dateiname:	0186-0408_160420_CAD_PL01-12x...-HP-L			
NTI AG, LinMot		Masstab 2:1		Zeichnungsnummer 0186-0408
				Format A3