





The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.



A	Document created	19.05.2025	JB	DG
Rev.	Change	Date	Author	Appr.

General tolerance DIN ISO 2768 - mK	Created by J.-E. Beekhuis	Status 19.05.2025/jb	Material		
LinMot®	File name 0380-0034_PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12	☐ Safety Rel.		Weight (g)	
		☐ UL-Rel.			
	Title, additional title PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12		Document type Assembly drawing		
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	Pick&Place / SM01-37Sx120 & SM01-37Sx60		Drawing number / Index 0380-0034A		
Template type: SW2020 Version: V1-1 SW_A2_hori_Sheet_format_V1-1	Art.No: 0300-1003		Scale 1:2		Sheet 1 / 3
		A2			

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.






Stage type	PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12	
Motor type	Horizontal: 0150-4406 SM01-37Sx120F-HP-R-320__SSCP	Vertical: 0150-6740 SM01-37Sx60-XP-R-100_BE20_MS04__SSCP
Stroke	220	100
Max. Force@48VDC [N]	255	128
Max. Force@72VDC [N]	255	128
Position resolution [mm]	0.005	0.005
Repeatability [mm]	±0.05	±0.05
Max. acceleration [m/s2]	< 15	< 15
Max. Velocity@48VDC [m/s]	1.5	1.5
Max. Velocity@72VDC [m/s]	2	2
Deviation	see installation guide	see installation guide
Moving mass [kg]	2.973	1.534
Module mass [kg]	5.118	4.228
Pillar mass [kg]	6.472	
Cable weight [kg/km]	83.0	
Cable tube weight [kg/m]	-	
Max. payload	see installation guide	see installation guide
Grease type - Motor	0150-1954 / 0150-1955 LU02	
Grease type - Bearing	0150-1954 / 0150-1955 LU02	
Grease type - MagSpring	0150-1954 / 0150-1955 LU02	

Accessories		
Stage type	PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12	
Motor type	Horizontal: 0150-4406 SM01-37Sx120F-HP-R-320__SSCP	Vertical: 0150-6740 SM01-37Sx60-XP-R-100_BE20_MS04__SSCP
Cable guide	Available: Not chosen	
Pillar system	Chosen: PP13_MT12	


A	Document created	19.05.2025	JB	DG
Rev.	Change	Date	Author	Appr.

General tolerance DIN ISO 2768 - mK	Created by J.-E. Beekhuis	Status 19.05.2025/jb	Material	
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	0380-0034_PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12		☐ Safety Rel.	Weight (g)
			☐ UL-Rel.	
	Title, additional title PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12 Pick&Place / SM01-37Sx120 & SM01-37Sx60 Art.No.: 0300-1003		Document type Datasheet	
Template type: SW2020 Version: V1-1 SW_A3_hori_Sheet_format_V1-1			Drawing number / Index 0380-0034A	
		Scale 3:10		Sheet 2 / 3
		A3		

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.



0150-4500 Z01-SF-30-SSC
Adapter dimensions



General tolerance DIN ISO 2768 - mK		Created by J.-E. Beekhuis	Status 19.05.2025/jb	Material	
LinMot®		0380-0034_PP13_320-37Sx120_100-37Sx60-BE20-MS04_MT12		☐ Safety Rel.	Weight (g) 18016.98
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach		Title, additional title PP13_320-37Sx120_ 100-37Sx60-BE20-MS04_MT12 Pick&Place / SM01-37Sx120 & SM01-37Sx60 Art.No.: 0300-1003		Document type Assembly drawing Drawing number / Index 0380-0034A	
Template type: SW2020 Version: V1-1 SW_A3_hori_Sheet_format_V1-1		Scale 1:2		Sheet 3 / 3	A3

Rev.	Change	Date	Author	Appr.
A	Document created	19.05.2025	JB	DG