




The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.



A	Document created	21.05.2025	JB	DG
Rev.	Change	Date	Author	Appr.

General Tolerance DIN ISO 2768 - mK	Created by J.-E. Beekhuis	Status 21.05.2025/jb	Material		
LinMot®	File name 0380-0043_PP13_375-48x150G_180-375x60-BE20-MS04_MT13	☐ Safety Rel.		Weight (g)	
		☐ UL-Rel.			
	NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	Title, additional title PP13_375-48x150G_ 180-375x60-BE20-MS04_MT13 Pick&Place / SM01-48x150 & SM01-37x60	Document type Assembly drawing Drawing number / Index 0380-0043A		
Template type: SW2020 Version: V1-1 SW_A2_hori_Sheet_format_V1-1	Art.No: 0300-1012	Scale 1:2		Sheet 1 / 3	A2

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.





Stage type	PP13_375-48x150G_180-37Sx60-BE20-MS04_MT13	
Motor type	Horizontal: 0150-4485 SM01-48x150G-HP-C-375_SSCP	Vertical: 0150-6711 SM01-37Sx60-XP-R-180_BE20_MS04_SSCP
Stroke	375	180
Max. Force@48VDC [N]	312	128
Max. Force@72VDC [N]	312	128
Position resolution [mm]	0.007	0.005
Repeatability [mm]	±0.05	±0.05
Max. acceleration [m/s2]	<15	<15
Max. Velocity@48VDC [m/s]	1.5	1.5
Max. Velocity@72VDC [m/s]	2	2
Deviation	see installation guide	see installation guide
Moving mass [kg]	6.648	1.930
Module mass [kg]	11.388	5.120
Pillar mass [kg]	7.000	
Cable weight [kg/km]	83.0	
Cable management weight [kg]	-	
Max. payload	see installation guide	see installation guide
Grease type - Motor	0150-1954 / 0150-1955 LU02	
Grease type - Bearings	0150-1954 / 0150-1955 LU02	
Grease type - MagSpring	0150-1954 / 0150-1955 LU02	

Accessories	
Stage type	PP13_375-48x150G_180-37Sx60-BE20-MS04_MT13
Motor type	Horizontal: 0150-4485 SM01-48x150G-HP-C-375_SSCP Vertical: 0150-6711 SM01-37Sx60-XP-R-180_BE20_MS04_SSCP
Cable guide	Available: Not chosen
Pillar system	Chosen: PP13_MT13



A	Document created	21.05.2025	JB	DG
Rev.	Change	Date	Author	Appr.

General tolerance DIN ISO 2768 - mK		Created by J.-E. Beekhuis	Status 21.05.2025/jb	Material				
LinMot® NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach		0380-0043_PP13_375-48x150G_180-37Sx60-BE20-MS04_MT13			☐ Safety Rel.		Weight (g)	
					☐ UL-Rel.			
		Title, additional title PP13_375-48x150G_ 180-37Sx60-BE20-MS04_MT13 Pick&Place / SM01-48x150 & SM01-37x60 Art.No.: 0300-1012			Document type Assembly drawing			
Drawing number / Index 0380-0043A								
Template type: SW2020 Version: V1-1 SW_A3_hori_Sheet_format_V1-1		Scale 1:4				Sheet 2 / 3		A3


The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.



0150-4500 Z01-SF-30-SSC
Adapter dimensions



1x 0150-5765 SM01-48-AP-37Sx60



A	Document created	21.05.2025	JB	DG
Rev.	Change	Date	Author	Appr.

General tolerance DIN ISO 2768 - mK	Created by J.-E. Beekhuis	Status 21.05.2025/jb	Material	
LinMot®	0380-0043_PP13_375-48x150G_180-37Sx60-BE20-MS04_MT13		☐ Safety Rel.	Weight (g) 24596.30
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach	Title, additional title PP13_375-48x150G_ 180-37Sx60-BE20-MS04_MT13 Pick&Place / SM01-48x150 & SM01-37x60 Art.No.: 0300-1012		Document type Assembly drawing	
Template type: SW2020 Version: V1-1 SW_A3_hori_Sheet_format_V1-1	Scale 1:3		Drawing number / Index 0380-0043A	
		Sheet 3 / 3		A3