




The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.



General tolerance DIN ISO 2768 - mK		Created by J.-E. Beekhuis	Status 28.08.2025/jb	Material	
LinMot®		File name 0380-0089_PP03_140-23x160H_80-23x160H-MS11_MT01_TC01	Title, additional title PP03_140-23x160H_ 80-23x160H-MS11_MT01_TC01 Pick&Place / DM01-23 & DM03-23		Art.No: 0300-0031
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach		Document type Assembly drawing		Drawing number / Index 0380-0089A	
Template type: SW2020 Version: V1-1 SW_A2_hori_Sheet_format_V1-1		Scale 2:3		Sheet 1 / 3	
				A2	

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.








Stage type	PP03_140-23x160H_80-23x160H-MS11_MT01_TC01	
Motor type	Horizontal: 0150-6231 DM01-23x160H-XP-R-140	Vertical: 0150-6109 DM03-23x160H-XP-R-80_CS10_MS11
Stroke	140	80
Max. Force@48VDC [N]	137	137
Max. Force@72VDC [N]	137	137
Position resolution [mm]	0.002	0.002
Repeatability [mm]	±0.05	±0.05
Max. acceleration [m/s2]	< 50	< 50
Max. Velocity@48VDC [m/s]	4.9	4.9
Max. Velocity@72VDC [m/s]	7.3	7.3
Deviation	see datasheet	see datasheet
Moving mass [kg]	0.800	0.800
Module mass [kg]	1.770	2.140
Pillar mass [kg]	1.530	
Cable weight [kg/km]	83.0	
Cable tube weight [kg/m]	0.084	
Max. payload	see datasheet	see datasheet
Grease type - Motor	0150-1954 / 0150-1955 LU02	
Grease type - Bearings	0260-0061 SKF LGFP 2	
Grease type - MagSpring	0150-1954 / 0150-1955 LU02	

Accessories		
Stage type	PP03_140-23x160H_80-23x160H-MS11_MT01_TC01	
Motor type	Horizontal: 0150-6231 DM01-23x160H-XP-R-140	Vertical: 0150-6109 DM03-23x160H-XP-R-80_CS10_MS11
Safety	Not available	Not available
Clean room	Available: not chosen	Not available
External sensor	Not available	Not available
Cover	Not available	Not available
Cable guide	Chosen: 0150-6704 PP03_TC01	
Pillar system	Chosen: 0150-6829 PP03_MT01	
Force sensor	Available: not chosen	Available: not chosen
Fan Kit	Not available	Not available

A	Document created	28.08.2025	JB	FH
Rev.	Change	Date	Author	Appr.

General tolerance DIN ISO 2768 - mK	Created by J.-E. Beekhuis	Status 28.08.2025/jb	Material	
LinMot® NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach Template type: SW2020 Version: V1-1 SW_A3_hori_Sheet_format_V1-1	0380-0089_PP03_140-23x160H_80-23x160H-MS11_MT01_TC01		☐ Safety Rel.	Weight (g)
			☐ UL-Rel.	
	Title, additional title PP03_140-23x160H_ 80-23x160H-MS11_MT01_TC01 Pick&Place / DM01-23 & DM03-23 Art.No.: 0300-0031		Document type Assembly drawing Drawing number / Index 0380-0089A	
Scale 1:3			Sheet 2 / 3	A3

The copyright to this document, which is personally entrusted to the recipient, remains with our company. Without our written permission, the document may not be copied nor reproduced nor communicated or made accessible to third parties without our written permission.



	A	Document created		28.08.2025	JB	FH
	Rev.	Change		Date	Author	Appr.

General tolerance DIN ISO 2768 - mK		Created by J.-E. Beekhuis	Status 28.08.2025/jb	Material			
LinMot®		File name 0380-0089_PP03_140-23x160H_80-23x160H-MS11_MT01_TC01		☐ Safety Rel. ☐ UL-Rel.		Weight (g)	
		Title, additional title PP03_140-23x160H_ 80-23x160H-MS11_MT01_TC01 Pick&Place / DM01-23 & DM03-23 Art.No.: 0300-0031		Document type Assembly drawing Drawing number / Index 0380-0089A			
NTI AG LinMot & MagSpring Bodenaeckerstrasse 2 CH-8957 Spreitenbach				Scale 3:5		Sheet 3 / 3	A2
Template type: SW2020 Version: V1-1 SW_A2_hori_Sheet_format_V1-1				