

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

SECTION 1. IDENTIFICATION

Product name : Klübersynth UH1 14-31

Article-No. : 096029

Manufacturer or supplier's details

Company name of supplier : Klüber Lubrication NA LP
9010 County Road 2120
Tyler, Texas 75707
USA
Phone: +1 903 534-8021
Fax: +1 903 581-4376

32 Industrial Drive
Londonderry, NH 03053
USA
Phone: +1 603 647-4104
Fax: +1 603 647-4106

E-mail address of person responsible for the SDS : mcm@us.kluber.com
Material Compliance Management

Emergency telephone number : +1-517-545-7070 NCEC

Recommended use of the chemical and restrictions on use

Recommended use : Grease

Restrictions on use : Restricted to professional users.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Substance / Mixture : Mixture

Chemical nature : Synthetic hydrocarbon oil
ester oil
aluminium complex soap
Mineral oil.

Components

Chemical name	CAS-No.	Concentration (% w/w)
(benzoato-O,O')hydroxy(octadecanoato-O,O')aluminium	54326-11-3	Trade secret (>= 5 - < 10)
White mineral oil (petroleum)	8042-47-5	Trade secret (>= 1 - < 5)
White mineral oil (petroleum)	8042-47-5	Trade secret (>= 1 - < 5)
disodium sebacate	17265-14-4	Trade secret (>= 1 - < 5)

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and water.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : No information available.
None known.

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon oxides
Oxides of phosphorus
Metal oxides
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Do not breathe vapours, aerosols.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Clean up promptly by sweeping or vacuum.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

Klübersynth UH1 14-31

Version 1.1	Revision Date: 03/27/2023	Date of last issue: 05/14/2021 Date of first issue: 05/14/2021	Print Date: 03/28/2023
----------------	------------------------------	---	---------------------------

Wash hands and face before breaks and immediately after handling the product.
Do not ingest.
Do not repack.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.

Conditions for safe storage : Store in original container.
Keep container closed when not in use.
Keep in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in accordance with the particular national regulations.
Keep in properly labelled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
(benzoato-O,O')hydroxy(octadecanoato-O,O')aluminium	54326-11-3	TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH (2018-03-20)
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH (2018-03-20)
White mineral oil (petroleum)	8042-47-5	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH (2013-03-01)
		TWA (Mist)	5 mg/m ³	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m ³	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m ³	NIOSH REL (2019-10-04)
White mineral oil (petroleum)	8042-47-5	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH (2013-03-01)
		TWA (Mist)	5 mg/m ³	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m ³	NIOSH REL (2019-10-04)

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
--	--	-----------	----------	---------------------------

Engineering measures : none

Personal protective equipment

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type P

Hand protection

Material : Nitrile rubber

Break through time : > 10 min

Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : white

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Combustible Solids

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : < 0.001 hPa (68 °F / 20 °C)

Relative vapour density : No data available

Relative density : 0.9 (68 °F / 20 °C)
Reference substance: Water
The value is calculated

Bulk density : No data available

Solubility(ies)

 Water solubility : insoluble

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : No data available

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Sublimation point : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : No conditions to be specially mentioned.

Incompatible materials : No materials to be especially mentioned.

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

Components:

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

toxicity

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

disodium sebacate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

White mineral oil (petroleum):

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

GLP : yes

disodium sebacate:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : no

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

disodium sebacate:

Species : Rabbit
Result : Irritating to eyes.
Assessment : Irritating to eyes.
Method : OECD Test Guideline 437
GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

Test Type : Maximisation Test
Species : Guinea pig

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

White mineral oil (petroleum):

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

disodium sebacate:

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: Ames test
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

White mineral oil (petroleum):

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

disodium sebacate:

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Carcinogenicity

Product:

Remarks : No data available

Components:

White mineral oil (petroleum):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

White mineral oil (petroleum):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

IARC OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

White mineral oil (petroleum):

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

White mineral oil (petroleum):

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

disodium sebacate:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

STOT - single exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

White mineral oil (petroleum):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

White mineral oil (petroleum):

NOAEL : 1,800 mg/kg
Exposure time : 90 d

Aspiration toxicity

Product:

This information is not available.

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Components:

White mineral oil (petroleum):

No aspiration toxicity classification

White mineral oil (petroleum):

May be fatal if swallowed and enters airways.

disodium sebacate:

No aspiration toxicity classification

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 1,000 mg/l
Exposure time: 21 d

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 28 d
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 1,000 mg/l
Exposure time: 21 d
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Toxicity to microorganisms : LC50 (Bacteria): > 1,000 mg/l
Exposure time: 40 h
Test Type: Growth inhibition

disodium sebacate:

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EL50 (Skeletonema costatum (marine diatom)): 38.7 mg/l
Exposure time: 72 h
Test Type: static test
Method: ISO 10253
GLP: yes

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

White mineral oil (petroleum):

Biodegradability : Primary biodegradation
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

White mineral oil (petroleum):

Biodegradability : Biodegradation: 31 %
Exposure time: 28 d

disodium sebacate:

Biodegradability : Result: Biodegradable
Biodegradation: 89 %

Klübersynth UH1 14-31

Version 1.1	Revision Date: 03/27/2023	Date of last issue: 05/14/2021 Date of first issue: 05/14/2021	Print Date: 03/28/2023
----------------	------------------------------	---	---------------------------

Exposure time: 28 d

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

White mineral oil (petroleum):

Partition coefficient: n-octanol/water : Pow: > 6

White mineral oil (petroleum):

Partition coefficient: n-octanol/water : log Pow: > 6

disodium sebacate:

Partition coefficient: n-octanol/water : log Pow: -4.9 (68 °F / 20 °C)
pH: 7.8

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Harmful to aquatic life with long lasting effects.

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Components:

White mineral oil (petroleum):

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

White mineral oil (petroleum):

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/27/2023

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily

Klübersynth UH1 14-31

Version	Revision Date:	Date of last issue: 05/14/2021	Print Date:
1.1	03/27/2023	Date of first issue: 05/14/2021	03/28/2023

mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.